

MY GORILLA GARAGE.com

GENERAL CARE AND MAINTENANCE SCHEDULE

***** GENERAL INFORMATION *****

MY GORILLA GARAGE Coating Systems demonstrate superior chemical and abrasion resistance and are designed to produce long-term, hard-wearing protection against chemical attack, dirt penetration, and everyday abuse. **MY GORILLA GARAGE** Coating Systems can be generally maintained with a routine program similar to any good-housekeeping procedures. Thorough sweeping and mopping to remove loose particles and soil along with the prompt removal of grease and other contaminants will prevent most **MY GORILLA GARAGE** Coating Systems from early deterioration. **Never use any cleaning products containing "Soy" as it will breakdown the top coat sealer causing premature product failure.**

***** DAILY MAINTENANCE *****

- Routine sweeping and/or mopping will prevent damage to the finish from the grinding effects of minute abrasive particles common to work areas. Over time, these particles can abrade the finish and cause premature gloss reduction. Mopping should only be done with a clean polyester mop and a mild soap added to water. Don't forget to use a healthy dose of "elbow grease" to break down contaminants and accumulations.
- if spilled, promptly remove grease, oil, gasoline, solvents and other contaminants.
- promptly RINSE OFF all chemical solutions that may attack the surface. Floors should be rinsed thoroughly with lots of clear, clean water.

***** WEEKLY MAINTENANCE *****

- ALL **MY GORILLA GARAGE** Coating Systems should be mopped on a regular basis using a mild soap added to water and then rinsed thoroughly with clean water. Water should be changed frequently and mops rinsed often. See the mopping instructions in the "DAILY MAINTENANCE" section above.
- Severe spillage or routine major contamination also requires special cleaning protocols. The following procedures for problem areas may also be applied in these instances...
- **CONTAMINATION:** Contaminated floors may require the use of a mechanical auto-scrubber or a firm bristle brush to reach the base of the texture. A strong concentrate of a mild degreaser should be used for these areas.
- **GREASE:** Greasy deposits are best removed using a heavy concentrate of a degreaser.
- **TIRE MARKS:** Scrub thoroughly with a stiff bristle brush using a mild degreaser.
- **STUBBORN DIRT OR STAINS:** Allow the cleaner time to penetrate and break down the problem area before scrubbing and rinsing off. This will increase the effectiveness of the cleaner and provide better results.
- **ALTERNATIVE CLEANERS:** Some cleaners currently available can have detrimental effects on the floor coating and could cause premature deterioration of the installed system. Always use a mild soap and water mixture and a mild degreaser diluted with water at a mixture of no more than 40% Degreaser and 60% water. Rinse thoroughly after degreaser application.

***** WAXING AND POLISHING *****

MY GORILLA GARAGE Coating Systems will provide a high gloss finish and need not be waxed or polished. However, should wear areas appear in heavy traffic areas over time, waxing or polishing with a standard commercial product may rejuvenate and enhance the overall appearance of the floor.